




# TECTUS® TE 303 3D P31-01

for unrebated residential doors





## TE 303 3D P31-01

for unrebated residential doors

### Hinge

up to 60 kg

### Product features

- completely concealed hinge system
- for timber, steel or aluminium frames
- for unrebated residential doors
- 3D adjustable (side + 3.0/-2.0 mm, height +/- 1.5 mm, compression +/- 1.0 mm)
- maintenance-free slide bearings

### Technical details

Load capacity	<b>i</b> 2 hinges per door leaf (1x2m)	60.0 kg
Width (frame)		29.0 mm
Width (door)		29.0 mm
Cutter diameter		24.0 mm
Opening angle		180°

### Finish

RAL 9003 Signal White (095), RAL 9005 Matte Black (107), Satin Chrome Look (F1) (124), Messing Effekt (131)

### Combination

Receiver	Casing frame	TE 303 3D FZ/42 P31-02
	Steel frame	TE 303 3D SZ P31-03

### Note

**i** The load capacity mentioned above refers to the use of 2 hinges per door leaf (1 x 2 m).

Door thicknesses of 36-40 mm allow for a centred routing.

### Corrosion resistance

Grade 2	moderate	Messing Effekt (131)
Grade 4	very high	RAL 9003 Signal White (095)
		RAL 9005 Matte Black (107)
		Satin Chrome Look (F1) (124)