

The list of cylinders recommended for PORTA doors				2020.03.26	
LP	Type of doors	Door leaf thickness (mm)	Type of escutcheon	Size of cylinder – dimension a/b	
				Opening outwards	Opening inwards
1	Interior rebated doors	40	Unico, Organic, Akcent, Modern, Next, Office, Caro, Royal, Topaz, Euforia Q, Cube, Brava, Elegant, Simple, Isa, Fussa, Julia, Divo Fit, Fado Fit, Oval, Kvadrat, Uno 3S, Due 3S, Mini Plus, Edel	26*/36	26/36*
2	Interior non-rebated doors	40		30/30	
3	Hide non-rebated, with reversed rebate	40	Unico, Organic, Akcent, Modern, Next, Office, Caro, Royal, Topaz, Euforia Q, Cube, Brava, Elegant, Simple, Isa, Fussa, Julia, Divo Fit, Fado Fit, Oval, Kvadrat, Uno 3S, Due 3S, Mini Plus, Edel	26*x36	
			Elegant, Simple, Isa, Fussa, Divo Fit, Fado Fit, Uno 3S, Due 3S	20*x30	
4	Interior Entrance doors Agate, Opal and Verte, FORES, technical doors Rw 27 dB	40	Agat, Agat Plus, Opal, Opal Plus, Cortes, Glober, Miro	solid 30*/35 with decorative milling 30*/40	solid 30/35* with decorative milling 30/40*
5	Interior Entrance doors Quartz, technical doors EI 30, EI 30 soft and Rw 32 dB	44	Agat, Agat Plus, Opal, Opal Plus, Cortes, Glober, Miro	solid 30*/40 with decorative milling 30*/45	solid 30/35* with decorative milling 30/40*
6	Interior Entrance doors Granite C	48-foil cover 44-in natural veneer	Porta Granit, Porta Granit Plus, Royal III class	30*/40 in natural veneer 30*/40	30/40*
7	Technical doors EI 60 Halspan	61	Agat, Agat Plus, Opal, Opal Plus, Cortes, Glober, Miro	35*/50	solid 40/45* with decorative milling 40/50*
8	Technical doors Rw 42 dB	69	Agat, Agat Plus, Opal, Opal Plus, Cortes, Glober, Miro	45*/45	40*/50
9	Steel Interior technical doors	40	Unico, Organic, Akcent, Modern, Next, Office, Caro, Royal, Topaz, Euforia Q, Cube, Brava, Elegant, Simple, Isa, Fussa, Julia, Divo Fit, Fado Fit, Oval, Kvadrat, Uno 3S, Due 3S, Mini Plus, Edel	26*/36	26/36*
10	Steel exterior technical doors	40	Oval, Kvadrat, Uno 3S, Due 3S, Mini Plus, Edel	26*/36	26/36*
11	Technical doors Steel EI 30	53	ECO Fire-rated	40*/35	40/35*
12	Technical doors Steel EI 60	67	ECO Fire-rated	45/45	45/45
13	Technical doors ENDURO rebated	40	Edel	26*/36	26/36*
14	Technical doors Aqua	40	Edel	30*/30	
15	Exterior doors Eco Polar	68	Opal, Opal Plus, Cortes, Glober	35*/55	40/50*
16	Exterior doors Eco Polar with multipoint lock	68	Cortes, Glober	35*/55	40/50*
17	Exterior doors Eco Polar Passive	80	Cortes, Glober	50*/50	50/45*
18	Exterior doors Eco Polar Passive with multipoint lock	80	Cortes, Glober	50*/50	50/45*
19	Exterior doors Eco Polar Passive with multipoint lock	80	Cortes + mini escutcheon	50*/30	35/45*
20	Porta Silence rebated	50	Opal, Opal Plus, Cortes, Glober	30*/45	30/40*
21	Porta Silence non-rebated	50	Opal, Opal Plus, Cortes, Glober	35/35	40/30*
22	Steel Safe	54	Porta Safe, Porta Opal only to Type II	45/30*	45*/30
23	Steel Energy Protect	68	Porta Safe	50/40*	45*/40
24	Granit RC3, Extreme RC3	50	Porta Safe	30*/40	30/40*
25	Extreme RC2	50	Agat, Agat Plus, Opal, Opal Plus, Cortes, Glober, Miro	30*/40	35/35*

Cylinder class selection must match product class.

* - side of possible knob use

a - dimension from narrower side of door
b - dimension from wider side of door

In non-rebated doors dimension a=b

